

## FUNCTION : APPLICATION

```
HTML_Parser_Cell (
Source_Field ;
Start_String ; Start_Occurrence ;
Middle_String ; Middle_Occurrence ; Middle_Gap ;
End_String ; End_Occurrence ; End_Gap
)
```

## FUNCTION : DEFINITION

```
Let ( [
$Position_Start = Position ( Source_Field ; Start_String ; 1 ; Start_Occurrence ) ;
$Position_Middle = Position ( Source_Field ; Middle_String ; $Position_Start ; Middle_Occurrence ) + Length ( Middle_String ) + 1 + Middle_Gap ;
$Position_End = Position ( Source_Field ; End_String ; $Position_Start ; End_Occurrence ) - 1 - End_Gap - $Position_Middle ] ;
Middle ( Source_Field ; $Position_Middle ; $Position_End )
)
```

## HTML : EXAMPLE

```
<form action='action.lasso' method='POST'>
<input type='hidden' name='Database' value='vendor.fp3'><input type='hidden' name='layout' value='Provider'>
<table border='0' cellpadding='0' cellspacing='2' width='268'>
<tr>
<td align='center' valign='top'>
<center>
<table border='0' cellpadding='0' cellspacing='2' width='420'>
<center>
<font size='4' face='Arial'><b>
A. Michael Krieger Inc.
</b></font><br>
<font size='3' face='Arial'>
441 Warren Street
</font><br>
<font size='3' face='Arial'>
Hudson ← , </font><font size='3' face='Arial'>
NY
</font><font size='3' face='Arial'>
12534
</font><br>
<font size='3' face='Arial'>
```

## SET FIELD: EXAMPLE

```
Set Field [ FR Designer::Fiche City;
HTML_Parser_Cell (
FR Designer::Fiche HTML ;
"<table border='0' cellpadding='0' cellspacing='2' width='420'>" ; 1 ;
"<font size='3' face='Arial'>" ; 2 ; 0 ;
"</font>" ; 3 ; 6
) ]
```

# FUNCTION : APPLICATION

```
HTML_Parser_Text (Source_Field ; Start_String ; Start_Occurrence ; Middle_String ; Middle_Occurrence ; Middle_Gap ; Middle_String_Bis ; End_String ; End_Occurrence ; End_Gap )
```

# FUNCTION :: DEFINITION

```
Let ( [  
$Position_Start = Position ( Source_Field ; Start_String ; 1 ; Start_Occurrence ) ;  
$Position_Middle = Position ( Source_Field ; Middle_String ; $Position_Start ; Middle_Occurrence ) + Length ( Middle_String ) + 1 + Middle_Gap ;  
$Position_End = Position ( Source_Field ; End_String ; $Position_Start ; End_Occurrence ) - 1 - End_Gap - $Position_Middle ;  
$html1 = Middle ( Source_Field ; $Position_Middle ; $Position_End ) ;  
$Position_End_Bis = Position ( $html1 ; Middle_String_Bis ; 1 ; 1 ) -1 ;  
$html2= If ( PatternCount ( $html1 ; Middle_String_Bis ) > 0 ;  
Middle ( $html1 ; 1 ; $Position_End_Bis ) ) ] ;  
$html2  
)
```

## **HTML : EXAMPLE**

## SET FIELD: EXAMPLE

```
Set Field [ srequette_BIENATTbyCour::IW Desc Chambre 1 Surface; HTML_Parser_Text (
srequette_BIENATTbyCour::Bien HTML ;
"<table border='0' cellspacing='0' cellpadding='0' width='100%'>" ; 2 ;
"Chambre 1 : " ; 1 ; -1 ; " m2;" ;
"</table>" ; 1 ; -1
)]
```